

K90TS-C3ABL



Features:

- Category 3
- Aesthetic design
- Compact size
- Dual wiring label, compatible with both T586A and T568B
- Special IDC technology for very effortless termination

Description:

RJ45 keystone jack, the IDC is 90 degrees to the jack cavity. This tool-free keystone jack requires no punch down tool for wire termination. The cap is specially designed for wire sorting and terminal protection. The ergonomic housing and cap have smooth surfaces, which makes termination by hand very easy and painless. The compact size is excellent for use on high-density snap-in patch panel (i.e. 24 port in 1U or 48 port in 2U). Standard color is white, but housing can be customized colors.

Specification:

| STANDARDS | |
|--------------|------------------------------------|
| Jack Cavity | FCC Part 68 Subpart F |
| Transmission | ANSI/EIA/TIA 568B.2, ISO/IEC 11801 |
| Wiring | T568A or T568B |

| MECHANICAL | |
|------------|---|
| IDC | 23~26 AWG conductor with Max 1.27mm insulation diameter |
| Durability | Jack can endure 750 cycles min. of mating cycles |

| PHYSICAL | |
|-----------|--------------------------|
| MATERIAL | UL 94V-0 Flame Retardant |
| Dimension | L30 x W16 x H19.2 (mm) |