

VGS-1602



Features:

- Auto-negotiation with link partners
- Auto-MDI/MDI-X detection
- Web-based management
- 19" rack mountable, 1U

Description:

16 Port 10/100/1000Base-T Ethernet Switch, with 1 SFP and Web-based Management.

Specification:

STANDARDS	
IEEE	802.3(10Base-T), 802.3u (100Base-TX), 802.3ab (1000Base-T), 802.3x, 802.1Q
Approval	FCC part 15 class A, CISPR 22 class A

TRANSMISSION	
Copper Port	16 Port Shielded RJ-45 jack, 10/100/1000Mbps full/half duplex, auto MDI/MDI-X detection, auto negotiation
Fiber Port	2 Port Mini-GBIC connector, 1000Mbps full duplex
Cable	Cat 3, 4, 5, 5e cable
VLAN Mode	Port-based VLAN, 802.1Q Tag-based VLAN
Buffer Memory	400K Bytes
MAC Address Table	8K Entries
Port Link Aggregation	Trunking Groups: 8 max., Ports/group: 8
QoS	2 Priority queues, Classification: Port-based, 802.1p-based, IP-based, DSCP-based



VOKONN TECHNOLOGY LTD.
4F., NO.20, Alley 16 Lane 298, Hsin-Ming Rd., Nei-Hu, Taipei,
114, Taiwan, R.O.C.

Tel:+886-2-2796-8123
Fax:+886-2-2793-7996
E-mail: info@vokonn.com

www.vokonn.com

LED Indication	Power status CPU status Copper Port: Speed, Link/Act Fiber Port: Speed, Link/Act
Management	Web-based interface for easy management System Setting Port status/statistics and configuration VLAN configuration QoS

PHYSICAL	
Operating Temperature	0°C ~ 40°C
Storage Temperature	-10°C ~ 60°C
Operating Humidity	10% ~ 90% non-condensing
Power Supply	100-240 VAC, 50~60Hz
Power Consumption	Max. 30 Watts
Dimension	L440 x W209 x H44 (mm)