

VGS-500



Features:

- Auto-negotiation with link partners
- Auto-MDI/MDI-X detection

Description:

5 Port 10/100/1000Base-T Ethernet Switch.

Specification:

STANDARDS	
IEEE	802.3(10Base-T), 802.3u (100Base-TX), 802.3ab (1000Base-T)
Approval	FCC part 15 class A, CISPR 22 class A

TRANSMISSION	
Copper Port	5 Port Shielded RJ-45 jack, 10/100/1000Mbps full/half duplex, auto MDI/MDI-X detection, auto negotiation
Cable	Cat 3, 4, 5, 5e cable
Data RAM Buffers	256K Bytes
MAC Address Table	4K Entries
Aging Time	300 sec.
LED Indication	Power status Copper Port: 100M Link/Act, 1000M Link/Act

PHYSICAL	
Operating Temperature	0°C ~ 40°C
Storage Temperature	-10°C ~ 60°C
Operating Humidity	10% ~ 90% non-condensing
Operating Voltage	7.5 VDC , 1.5A



VOKONN TECHNOLOGY LTD.
4F., NO.20, Alley 16 Lane 298, Hsin-Ming Rd., Nei-Hu, Taipei,
114, Taiwan, R.O.C. Tel:+886-2-2796-8123
Fax:+886-2-2793-7996
E-mail: info@vokonn.com

www.vokonn.com

Power Consumption	Max. 8.5 Watts
Dimension	L171 x W98 x H29 (mm)